



ACCESSORIES



	Article number	Description	Housing color	Voltage	Item weight
1	80100	5-pin horizontal plug connector	black	12 V; 24 V	80 g
2	3928002	5-pin vertical plug connector	black	12 V; 24 V	80 g
3	83928003	5-pin male plug	black	12 V; 24 V	30 g
4	80105	horizontal base with cap	black	12 V; 24 V	30 g
5	83928002	vertical base with cap	black	12 V; 24 V	30 g

Vertical and horizontal mounted watertight plug connectors for any accessory installed on deck that needs to be removed on a regular basis.

Can also be used for accessories on the mast, for easy connection of conductors when mast is stepped or removed.

Application

Inside and outside (-30°C - +130°C).

Housing

Polycarbonate black, shock-resistant, non-corrosive, non-magnetic, seawater resistant.

Equipment

IP 65

Protection

IP 65

Mounting

With 2/4 screws, 4 mm / 0.16" (not included).

Electric

4 + 1 wire; 4 x 16 Amp.; max. 42 V; cable entry PG 11 (cable 6 mm - 10 mm / 0.25" - 0.4").

ACCESSORIES

ACCESSORIES



Nav-Switch

It does not get any simpler to control the proper navigation light combinations under sailing and powering applications.

Application

An ingenious multi-switch for clear and error-free operation of navigation, decks and instrument lighting. A simple solution for added safety on board.

Housing

When it is getting dark while under sail you can turn on the tricolor sailing light by a quarter of a turn with the Nav-Switch from the steering pedestal. Under engine propulsion by turning the Nav-Switch another quarter turn, the tricolor sailing light is replaced by the correct steaming lights. You have reached your anchorage and you turn the Nav-Switch to clearly visible anchor symbol. Masthead and running lights are thus switched off and the anchor light is illuminated at the top of the mast. In every switch position and additional function lighting (e.g. deck lighting), can be switched on or off by pulling or pushing the Nav-Switch. The instrumental lighting is switched on at the same time as the navigational lighting.

Protection

IP 66

The position of the Nav-Switch is flexible and with its protection IP 66 it can be used outside at the steering pedestal.

Article number	Description	Voltage	Item weight
3928500	NAV-Switch	12 V; 24 V	120 g



ACCESSORIES



Data

Electric	12V/24V, 8A
Protection	IP 66
Temperature	-40°C/+85°C
Special plastic	PA 6

mm / inch

